



Reliability In Action

D26H

TRACK-TYPE DOZER

Operating weight: 25000 kg

Engine power: 203 kW



Premium & Reliable

Efficient & Energy-saving

Comfortable & Convenient

D26H

Main specifications

Main parameters			
Operating weight (kg)	25000	Rated engine speed (r/min)	1800
Ground Pressure (kPa)	65.4	Minimum fuel consumption, g/(kW·h)	198
Ground Clearance (mm)	400	Maximum torque (N·m) / speed (r/min)	1280/1500
Turning Radius (mm)	4125	Displacement (L)	7755
Maximum gradability (°)	30	Emissions standard	GB20891-2007
Maximum traction force (kN)	387	Chassis system	
Travelling speed(F/R) (km/h)	11/11	Number of track rollers (per side)	7
Overall dimension and working range		Number of carrier rollers (per side)	2
Overall length (mm)	5797/7850(with rear ripper)	Number of track shoes (per side)	40
Overall width (mm)	3595	Working device	
Overall height (mm)	3425	Std. flow rate (L/min)	250
Track ground contact length (mm)	2945	System working pressure (Mpa)	21
Track Gauge (mm)	2000	Maximum lifting speed (m/s)	0.3
Track Width (mm)	560	Maximum lifting force (kN)	130
Engine		Maximum pushing force (kN)	71.2
Engine model	BFM8-28T2	Blade	
Engine type	In-line, 6-cylinder, water-cooled, 4-stroke	Capacity (m³)	6.8
Bore / Stroke (mm)	110/136	Width (mm)	3595
Rated engine power (kW)	203	Height (mm)	1536
		Ripper	
		Maximum lifting height (mm)	1165
		Maximum cutting depth (mm)	572
		Maximum tilting height (mm)	570
		Cutting angle (°)	55
		Total weight (kg)	2420
		Maximum lifting height (mm)	665
		Maximum cutting depth (mm)	948
		Departure angle (°)	20.5
		Working width (mm)	1136
		Ripper tooth gauge (mm)	/
		Service capacities	
		Fuel (L)	500
		Hydraulic oil (L)	140
		Engine crankcase oil (L)	33
		Final drive (per side) (L)	35
		Pivot box (per side) (L)	2.5
		Cooling system (L)	40
		AC system refrigerant (kg)	1.4

*SDLG reserves the right to change specifications and materials at any time without prior notification. Features of the machine in photos may include additional equipment. If you need more information and available options, please contact your local distributor or SDLG.



Shandong Lingong Construction Machinery Co., Ltd.

Add: Lingong Industry Park, Economic Development Zone, Linyi, Shandong, P.R.China

Tel: 0086-531-66590505 Fax: 0086-531-66590505 E-mail: export@sdlg.com Website: www.sdlg.com